

KFL-10P

Visual Fault Locator



Key Features

- Bright red laser at 650nm
- Pulsed and CW operation
- Outpower: 1mw,10mw,20mw,30mw
- 2.5mm universal connector
- 60 hours of operation(1mW)
- Pocket size design
- 1.25 mm adapter for LC (optional)

Time saving and high efficiency



Support four interface fiber types



ST



FC



SC



LC (optional)

PRODUCT SPECIFICATION:

Model	KFL-10P			
output power	1mW	10mW	20mW	30mW
Output wavelength	650nm			
Laser type	FP-LD			
2Hz	Yes			
Connector type	2.5mm universal connector for FC,SC,ST;1.25mm LC optional			
working temperature	-20~50°C			
Storage temperature	-20~50°C			
Battery	AA*2			
weight	80g			
Shape size	180*24mm			

CONTACT US:

KomShine Technologies Limited

HEAD OFFICE:

205 D-Building, Qinheng Technology Park, Ningshuang road, Nanjing, Jiangsu, China

TEL: + 86 25 8687 1288

FAX: + 86 25 8687 1288

www.komshine.com

sales@komshine.com

- * Komshine reserves the right to improve, enhance, or modify the features and specifications of KomShine products without prior notification.
- * Company and product names appearing in this catalogue are registered marks or trademarks of respective companies.
- * This catalogue is printed using environmentally friendly paper and ink.