


KPM-35 & KLS-35

Optical Power Meter & Light Source



Key Features

- High Precision
- Highly accurate unit offering 6 calibrated wavelengths
- Interchangeable connectors
- Durable and reliable design
- Easy-to-use interface for error-free testing
- Rubber armor protection



Backlight display



One key start



Automatic shutdown



Plug and play



6 calibrated wavelengths



Silica gel protect pads

PRODUCT FEATURES



Drop proof



Hand-held



Bracket



Rubber protection

KPM-35



Interface accessories



SC



FC



ST

Wavelength(nm)	800~1700nm
Measurement Range	-70+3dBm / -50~+26dBm
Optical Connector	FC+SC+ 2.5mm universal (1.25mm for LC is Optional)
Power Supply	Alkaline Battery(3 AA 1.5V batteries) (Purchased separately)
Display Units	dB / dBm / w
Resolution (dB)	0.01
Dimensions / Weight	160x85x45mm /220 g

KLS-35



Interface accessories



SC



FC



ST

Wavelength(nm)	SM 1310/1550nm (KLS-35S)
	MM 850/1300/1310/1550nm (KLS-35MS)
	PON 1310/1490/1550nm (KLS-35P)
Typical Output Power	-5dB
Optical Connector	FC+SC+ 2.5mm universal (1.25mm for LC is Optional)
Power Supply	Alkaline Battery(3 AA 1.5V batteries) (Purchased separately)
Output Stability	±0.05dB/15mins; ±0.1dB/ 8hours
Modulation Frequencies	CW,270Hz,1KHz,2KHz
Dimensions / Weight	160x85x45mm / 220g

PACKAGING DISPLAY:



CONTACT US:

KomShine Technologies Limited

HEAD OFFICE:

205 D-Building, Qinheng Technology Park, Ningshuang road, Nanjing, Jiangsu, China

TEL: + 86 25 8687 1288

FAX: + 86 25 8687 1288

www.komshine.com

sales@komshine.com

* Komshine reserves the right to improve, enhance, or modify the features and specifications of KomShine products without prior notification.

*Company and product names appearing in this catalogue are resisterd marks or trademarks of respective companies.

* This catalogue is printed using environmentally friendly paper and ink.