

## KPM-25m & KLS-25m

Mini Size Power Meter & Light Source



### Key Features

- Pocket size design
- Highly accurate unit offering 6 calibrated wavelengths
- Interchangeable connectors
- Durable and reliable design
- Easy-to-use interface for error-free testing
- Rubber armor protection



Backlight display



One key start



Automatic shutdown



Plug and play



Super long standby



Silica gel protect pads

# PRODUCT FEATURES



Drop proof



Hand-held



Bracket



Rubber Protection

## KPM-25M



Interface accessories



SC



FC



ST

Wavelength(nm)	800~1700nm
Measurement Range	-70+3dBm / -50~+26dBm
Optical Connector	2.5mm universal+SC (1.25mm for LC is Optional)
Power Supply	Alkaline Battery(2 AAA 1.5V batteries) (Purchased separately)
Display Units	dB / dBm / w
Resolution (dB)	0.01
Dimensions / Weight	130x65x35mm / 180g

# KLS-25M



Interface accessories



SC



FC



ST

Wavelength(nm)	850+1300nm / 1310+1550nm
Typical Output Power	-5dB
Optical Connector	2.5mm universal+SC (1.25mm for LC is Optional)
Power Supply	Alkaline Battery(2 AAA 1.5V batteries) (Purchased separately)
Output Stability	±0.05dB/15mins; ±0.1dB/ 8hours
Modulation Frequencies	CW,270Hz,1KHz,2KHz
Dimensions / Weight	130x65x35mm / 180g

## Packaging display:



## Contact Us:

KomShine Technologies Limited

### Head Office:

205 D-Building, Qinheng Technology Park, Ningshuang road,  
Nanjing,  
Jiangsu, China  
TEL: + 86 25 8687 1288  
FAX: + 86 25 8687 1288  
www.komshine.com

\* KomShine reserves the right to improve, enhance, or modify the features and specifications of KomShine products without prior notification.\*

Company and product names appearing in this catalogue are registered marks or trademarks of respective companies.

\* This catalogue is printed using environmentally friendly paper and ink.